



**CONFORMITY CERTIFICATE  
OF FACTORY PRODUCTION CONTROL**

Certificate number: 1035-CPR-ES074275

In compliance of the Regulation No 305/2011 of the European Parliament and of the Council of 9 March 2011 laying down harmonised conditions for the marketing of construction products, it has been stated that the product:

**ALUMINIUM AND ALUMINIUM ALLOYS**

Manufactured by: **ALAS IBERIA S.L.U.**

In the factory: **AVD. LAVIANA S/N. CIAÑO – LANGREO (ASTURIAS)**

They are submitted by the manufacturer to the initial type testing of the product and a factory production control, and that the notified body Bureau Veritas Certification has performed the initial inspection of the factory and of the factory production control and performs the continuous surveillance, assessment and approval of the factory production control established in the harmonized standard EN 15088:2005.

This certificate attests that all provisions concerning the attestation of factory production control described in the Annex ZA of the harmonized standard concerned, and it authorizes the manufacturer or its agent to fix the CE marking.

This certificate remains valid as long as the conditions laid down in the harmonised standard concerned or the manufacturing conditions in the factory or the FPC itself are not modified significantly until 2019, August 08<sup>th</sup>.

Place and date of initial issuing: Madrid 2016, August 09<sup>th</sup>

Signed:

**Mónica Botas**  
Certification Manager

Bureau Veritas Iberia, S.L.  
Edificio Caoba. C/ Valportillo Primera 22-24  
Polígono Industrial La Granja  
28108 – Alcobendas (MADRID)  
Notified Body 1035  
Control Body accredited by ENAC with accreditation N°OC-P / 005



**ANNEX TO CERTIFICATE Nb<sup>er</sup> 1035-CPR-ES074275**

Date: 2016, 09 August

<i>EN 15088:2005- Aluminium and aluminium alloys. Structural products for construction works. Technical conditions for inspection and delivery</i>				
Description				
ALLOY	TREATMENT	DIMENSIONS (mm)	LENGTH (m)	THICKNESS (mm)
AW6060	T5,T6	Tube, Profiles and Bars enrolled in a circle of diameter from 11mm up to 425 mm measures.	Maximun L= 14 m	107gr/m to 25Kgr/m
AW6005				
AW6063	T5			
AW6082	T6			
AW6106	T6			

Signed:

Mónica Botas  
Certification Manager