



BUREAU  
VERITAS

Bureau Veritas Certification

# CONFORMITY CERTIFICATE OF FACTORY PRODUCTION CONTROL

Certificate N°: 1035-CPR-ES074275

In compliance of the Regulation No 305/2011 of the European Parliament and of the Council of 9 March 2011 laying down harmonized conditions for the marketing of construction products, it has been stated that the product:

## ALUMINIUM AND ALUMINIUM ALLOYS

Manufactured by: **ALAS IBERIA, S.L.U.**  
AVD. DE LAVIANA, S/N, 33900, CIAÑO-LANGREO,  
ASTURIAS (ESPAÑA).

In the factory: AVD. DE LAVIANA, S/N, 33900, CIAÑO-LANGREO,  
ASTURIAS (ESPAÑA)

They are submitted by the manufacturer to the initial type testing of the product and a factory production control, and that the notified body Bureau Veritas Certification has performed the initial inspection of the factory and of the factory production control and performs the continuous surveillance, assessment and approval of the factory production control established in the harmonized standard concerned.

This certificate attests that all provisions concerning the attestation of factory production control described in the Annex ZA of the harmonized standard concerned, and it authorizes the manufacturer or its agent to fix the CE marking.

This certificate remains valid as long as the conditions laid down in the harmonised standard concerned or the manufacturing conditions in the factory or the FPC itself are not modified significantly

Initial date of issue: 2016 / 08 / 09  
Date of update: 2023 / 03 / 29  
Expiration date: 2025 / 08 / 08



Mónica Botas  
Certification manager







BUREAU  
VERITAS

Bureau Veritas Certification

# ANNEX OF CERTIFICATE N° 1035-CPR-ES074275

Date: 2023 / 03 / 29

EN 15088:2005- Aluminium and aluminium alloys. Structural products for construction works. Technical conditions for inspection and delivery					
Description: EXTRUDED PROFILE					
ALLOY	TREATMENT	TECHNICAL PERFORMANCES	DIMENSIONS (mm)	LENGTH (m)	THICKNESS (mm)
AW-6060	T5, T6	EN AW-6060	Profiles enrolled in a circle of diameter from 11mm up to 425 mm measure.	Maximun L= 14 m	Range: 107gr/m hasta 25kgr/m
AW-6063	T5, T6	EN AW-6063			
AW-6106	T6	EN AW-6106			
AW6005A	T5, T6	EN AW 6005A			
AW-6082	T5, T6	EN AW 6082			
AW-6101	T6	EN AW-6101			



Mónica Botas  
Certification manager

